



TYPICAL APPLICATIONS

Shoulder work  
Utility operations

GENERAL NOTES

This Standard is used where at any time, any vehicle, equipment, workers or their activities require an intermittent or continuous moving operation on the shoulder, where the average speed is 2 km/h (1 mph) or less.

\* Minimum distance is 60 m (200'). Maximum distance to be determined by the Engineer but should not exceed 1/2 the length required for one normal working day's operation, or 6400 m (4 miles) which ever is less.

If the work operation does not exceed 60 minutes, traffic control may be in accordance with Standard 701301.

All dimensions are in millimeters (inches) unless otherwise shown.

SYMBOLS

Work area

Sign

● Flagger with traffic control sign when required

DATE	REVISIONS
1-1-97	Renum. Standard 2305-9.
	Deleted orange flags.
5-1-95	Rev. WORKER sign and
	flagger symbols to be
	filled in.

OFF-RD MOVING OPERATIONS  
2L, 2W DAY ONLY  
FOR SPEEDS ≥ 45 MPH

STANDARD 701011

Illinois Department of Transportation

APPROVED January 1, 1997

ENGINEER OF OPERATIONS

APPROVED January 1, 1997

ENGINEER OF DESIGN AND ENVIRONMENT

ISSUED 1-1-97